



B41827B8226M Information

Heisener.com

Part Number B41827B8226M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41827B8226M Specifications

Manufacturer Part Number B41827B8226M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41827 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency -		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41827 Capacitance 22μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Manufacturer Part Number	B41827B8226M
Aluminum Electrolytic Capacitors Package Radial, Can Series B41827 Capacitance 22µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency 100mA @ 120Hz	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41827Capacitance $22\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $100\text{mA} @ 120\text{Hz}$	Category	Capacitors
SeriesB41827Capacitance $22μF$ Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $100mA @ 120Hz$		Aluminum Electrolytic Capacitors
Capacitance $22μF$ Tolerance $±20%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs } @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $100mA @ 120Hz$	Package	Radial, Can
Tolerance $\pm 20\%$ Voltage - Rated $63V$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Polarization Polar Applications General Purpose Ripple Current - Low Frequency $100\text{mA} @ 120\text{Hz}$	Series	B41827
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 100mA @ 120Hz	Polarization	Polar
	Applications	General Purpose
Ripple Current - High Frequency -	Ripple Current - Low Frequency	100mA @ 120Hz
	Ripple Current - High Frequency	-
Impedance -	Impedance	-
Lead Spacing -	Lead Spacing	-
Size / Dimension -	Size / Dimension	-
Height - Seated (Max)	Height - Seated (Max)	-
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

B41827B8226M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41827B8226M Payment Methods



















B41827B8226M Shipping Methods













If you have any question about B41827B8226M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com