



B41828A4158M Information

Heisener.com

For Reference Only

Part Number B41828A4158M
Manufacturer EPCOS (TDK)
Category Capacitors

Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 1500UF 20% 16V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41828A4158M Specifications

Manufacturer Part Number B41828A4158M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41828 Capacitance 1500µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Operating Temperature - Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41828 Capacitance 1500µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	B41828A4158M
Package Radial, Can Series B41828 Capacitance 1500µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size Mounting Type Talea Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41828 Capacitance 1500µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
SeriesB41828Capacitance1500μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance 1500µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Raisstance)	Series	B41828
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 100 100 100 100 100 100 100 1	Capacitance	1500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case - Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C - Cancel Purpose General Purpose	Voltage - Rated	16V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar General Purpose	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose - Cannot Purpose - Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case General Purpose - General Purpose - General Purpose - Through Hole Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Card Spacing - Card Size / Dimension - Card Surface Mount Land Size - Card Surface Mount Land Surface Mount La	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	-
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	-
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41828A4158M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41828A4158M Payment Methods



















B41828A4158M Shipping Methods













If you have any question about B41828A4158M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com