



### **B41828A6106M Information**

Heisener.com

Part Number B41828A6106M
Manufacturer EPCOS (TDK)
Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 10UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B41828A6106M Specifications**

Manufacturer Part Number         B41828A6106M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B41828           Capacitance         10µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         48mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	2 11020110110111 Specifications	
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can  Series B41828 Capacitance 10µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	B41828A6106M
PackageRadial, CanSeriesB41828Capacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency48mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41828Capacitance10μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency48mA @ 120HzRipple Current - High Frequency-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series         B41828           Capacitance         10μF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         48mA @ 120Hz           Ripple Current - High Frequency         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         10μF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         48mA @ 120Hz           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 50V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 48mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Raidla, Can	Series	B41828
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Polar  2000 Hrs @ 105°C  Coneral Purpose  General Purpose  48mA @ 120Hz  7000mm  1000mm  1000m	Capacitance	10μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  - Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  - Lifetime @ Temp.  2000 Hrs @ 105°C  Connect Connec	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  - Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 105°C  - Condended  - Condended	Voltage - Rated	50V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency AsmA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing O.079" (2.00mm) Size / Dimension O.197" Dia (5.00mm) Height - Seated (Max) O.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  Ripple Current - Low Frequency	Operating Temperature	-
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  48mA @ 120Hz  -  48mA @ 120Hz  -  Through Hole  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	48mA @ 120Hz
Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **B41828A6106M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B41828A6106M Payment Methods**



















# **B41828A6106M Shipping Methods**













If you have any question about B41828A6106M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com