



B41828B5228M Information

Heisener.com

Part Number B41828B5228M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2200UF 20% 25V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41828B5228M Specifications

Manufacturer Part Number Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41828 Capacitance 2200µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Lead Spacing Size / Dimension		
Category Category Capacitors Aluminum Electrolytic Capacitors Radial, Can Series Radial, Can Series B41828 Capacitance 2200µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Inpedance Lead Spacing Capacitors Radial, Can Aluminum Electrolytic Capacitors Radial, Can Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Radial, Can Aluminum Electrolytic Capacitors Radial, Can Aluminum Electrolytic Capacitors Radial, Can Electrolytic Capacitors Radial, Can Aluminum Electrolytic Capacitors Radial, Can Electrolytic Capacitors Radial,	Manufacturer Part Number	B41828B5228M
Package Radial, Can Series B41828 Capacitance 2200µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency 1.223A @ 120Hz Lied Spacing -	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41828Capacitance2200μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.223A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing-	Category	Capacitors
Series B41828 Capacitance 2200µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -		Aluminum Electrolytic Capacitors
Capacitance2200μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.223A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -	Series	B41828
Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -	Capacitance	2200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Lead Spacing - 2000 Hrs @ 105°C - Common Applications Polar - Common Applications - Lead Spacing - Lead Spacing - Lead Spacing	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -	Voltage - Rated	25V
Operating Temperature - Polarization Polar Polarization General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Lead Spacing - Polarization - Pola	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.223A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing -	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.223A @ 120Hz - Lead Spacing	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing -	Applications	General Purpose
Impedance-Lead Spacing-	Ripple Current - Low Frequency	1.223A @ 120Hz
Lead Spacing -	Ripple Current - High Frequency	-
	Impedance	-
Size / Dimension -	Lead Spacing	-
	Size / Dimension	-
Height - Seated (Max) -	Height - Seated (Max)	-
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

B41828B5228M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41828B5228M Payment Methods



















B41828B5228M Shipping Methods













If you have any question about B41828B5228M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com