

B41851A5107M7

Request a Quote

B41851A5107M7 Information

Heisener.com	Part Number	B41851A5107M7	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 100UF 20% 25V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
I of Reference Only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41851A5107M7 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41851 Capacitance 100µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 2.7 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance100μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41851A5107M7
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance100µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Size / Dimension0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41851Capacitance100µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature90a0 Hrs @ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency40mA @ 120HzRiple Current - High Frequency0.98" (2.50mm)Size / Dimension0.948" Dia (6.30mm)Size / Dimension0.428" Dia (6.30mm)Sirface Mount Land Size-Mounting TypeHolePackage / CaseKaila, Can	Category	Capacitors
SeriesB41851Capacitance100µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.098° (2.50mm)Size / Dimension0.448° Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.448" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	B41851
Voltage - Rated25VESR (Equivalent Series Resistance)2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.428" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Capacitance	100µF
Construction2.7 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFriough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	2.7 Ohm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency140mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	140mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41851A5107M7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41851A5107M7 Payment Methods



B41851A5107M7 Shipping Methods



If you have any question about B41851A5107M7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com