



B41851A6335M8 Information

Heisener.com

Part Number B41851A6335M8 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3.3UF 20% 50V RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41851A6335M8 Specifications

Manufacturer Part Number B41851A6335M8 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41851 Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41851 Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	B41851A6335M8
Package Radial, Can Series B41851 Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41851 Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41851 Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 3.3µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 60 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polar Application Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Series	B41851
Voltage - Rated50VESR (Equivalent Series Resistance)60 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	3.3µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 2000 Hrs @ 120Hz 2000 Hrs @ 105°C - Ceneral Purpose General Purpose 25mA @ 120Hz	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C Out of 105°C General Purpose 25mA @ 120Hz 109Hz 25mA @ 120Hz 109Hz 109Hy 109Hy 109Hole 109Hy 109Hole 109Hy 109Hole 109Hy 109Hole 109Hy 109Hole 109Hy 109H	Voltage - Rated	50V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Pola	ESR (Equivalent Series Resistance)	60 Ohm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	25mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41851A6335M8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41851A6335M8 Payment Methods



















B41851A6335M8 Shipping Methods













If you have any question about B41851A6335M8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com