

B41851A7476M8

B41851A7476M8 Information

Heisener.com	 B41851A7476M8 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 47UF 20% 35V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41851A7476M8 Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseKabial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B41851A7476M8
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.197" (5.00mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41851Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CPolarizationFolarApplicationsGeneral PurposeRiple Current - Low Frequency93mA @ 120HzRiple Current - High Frequency0.197" (5.00mm)Siz / Dimension0.197" Dia (5.00mm)Siz / Dimension0.472" (12.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseKadial, Can	Category	Capacitors
SeriesB41851Capacitance47μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Bight - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	B41851
Voltage - Rated35VESR (Equivalent Series Resistance)4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	47µF
Constraint4.9 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Voltage - Rated	35V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	4.9 Ohm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	93mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41851A7476M8 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41851A7476M8 Payment Methods





If you have any question about B41851A7476M8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com