

B41851A9224M

Request a Quote

B41851A9224M Information

(A Heisener.com	Part Number	B41851A9224M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
A Construction	Description	CAP ALUM 0.22UF 20% 100V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41851A9224M Specifications

Manufacturer Part Number B41851A9224M Manufacturer EPCOS (TDK) Category Capacitors Alminum Electrolytic Capacitors Alminum Electrolytic Capacitors Package Radia, Can Streis B41851 Capacitance 0.22µF Tolerance 2000 Voltage - Rated 0.0V ESR (Equivalent Series Resistance) 54 Ohm @ 120Hz Operating Temperature 2000 Hrs @ 105°C Operating Temperature 000 VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance0.22µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzDiferime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Nounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41851A9224M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41851Capacitance.22µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature.PolarizationGeneral PurposeApplications3.4mA @ 120HzRipple Current - Low Frequency.Impedance.Lided Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Size / Dimension0.472" (12.00mm)Surface Mount Land Size.Mounting TypeRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41851Capacitance0.22µFTolerance20%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzDierating @ Temper0000 Hrs @ 105°COperating Temperature0000 Hrs @ 105°CApplicationsPolarRipple Current - Low FrequencyGeneral PurposeRipple Current - High Frequency0.47°C (200mm)Size / Dimension0.19°F (200mm)Size / Dimension0.19°F (200mm)Size / Dimension0.47°C (200mm)Size / Dimension0.47°C (200mm)Size Addunt Land Size-Mouting TypePincugationPackage / CaseMaida, Can	Category	Capacitors
SeriesB4181Capacitance0.22µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency3.4mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFrough HolePokage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance0.22µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Liad Spacing0.079° (2.00mm)Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.472° (12.00mm)Surface Mount Land Size-Mounting TypeFinough HeightPackage / CaseRatial, Can	Package	Radial, Can
Tolerance±2%Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.4mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Hight - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can	Series	B41851
Voltage - Rated100VESR (Equivalent Series Resistance)754 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Hounting TypeFnough HolePackage / CaseRatial, Can	Capacitance	0.22µF
LESR (Equivalent Series Resistance)754 Ohm @ 120HzESR (Equivalent Series Resistance)2000 Hrs @ 105°CLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.472" (12.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	Voltage - Rated	100V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	754 Ohm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency3.4mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In or a randomRipple Current - High Frequency-Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	3.4mA @ 120Hz
Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41851A9224M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41851A9224M Payment Methods





If you have any question about B41851A9224M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com