

B41858C4477M000

Quote

B41858C4477M000 Information

	Part Number	B41858C4477M000	
www.heisener.com	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 470UF 20% 16V RADIAL	6 S O
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41858C4477M000 Specifications

Manufacturer Part Number B41858C4477N000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41858 Capacitance 470µF Tolerance 420% Voltage - Rated I6V ESR (Equivalent Series Resistance) 129 mOhm @ 10kHz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature 55°C ~ 105°C Polarization Automotive Ripple Current - Low Frequency Automotive Impedance 113 mOhms Lead Spacing 0.197° (5.00mm) Size / Dimension 0.532° (13.50mm) Size / Dimension 5.532° (13.50mm) Height - Seated (Max) 5.532° (13.50mm)	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41858Capacitance470µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)129 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency113 mOhmsLead Spacing0.197" (5.00mm)Size / Dinension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41858C4477M000
IdentifyAluninum Electrolytic CapacitonsPackageRadial, CanSeriesB41858Capacitance470µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)129 mOhm @10kHzLifetime @ Temp.5000 Hrs @105°COparing Temperature55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency746mA @100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Kirder Mount Land Size-Hight - Seated (Max)0.532" (13.50mm)Mounting TypeFrequencyRackage / CaseMaid, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41858Capacitance470µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)29 mOhm @ 10kHzDierating @ Tempe.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsAutomtiveRipple Current - Low Frequency-Impedance113 mOhmsLad Spacing0.94" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension-Murding Type-Mounting TypeFrouge MathematicaPackage / CaseRadia, Can	Category	Capacitors
SeriesB41858Capacitance470µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)129 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency113 mOhmsIngedance113 mOhmsSize / Dimension0.394" Dia (10.00mm)Size / Dimension0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila (Can		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)129 mOhm @ 10kHzESR (Equivalent Series Resistance)5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Inpedance13 mOhmsIngedance0.197" (5.00mn)Size / Dimension0.394" Dia (10.00mm)Size / Dimension-Kurface Mount Land Size-Mounting TypeFrouge HolePackage / CaseKaia, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated16VESR (Equivalent Series Resistance)129 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Pounting TypeFnrough HolePackage / CaseRadial, Can	Series	B41858
Voltage - RatedI6VESR (Equivalent Series Resistance)129 mOhm @ 10kHzESR (Equivalent Series Resistance)5000 Hrs @ 105°CLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Kipple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsIcad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	470µF
FSR (Equivalent Series Resistance)129 mOhm @ 10kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)5.32" (13.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseReside CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	129 mOhm @ 10kHz
PolarizationPolarPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsAutomotiveApplications-Ripple Current - Low Frequency746mA @ 100kHzRipple Current - High Frequency113 mOhmsImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
InRipple Current - Low Frequency-Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency746mA @ 100kHzImpedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance113 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	746mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	113 mOhms
Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.532" (13.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can
		Report errors?

B41858C4477M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41858C4477M000 Payment Methods



If you have any question about B41858C4477M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com