

B41868W8337M

B41868W8337M Information

Heisener.com	 B41868W8337M EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 63V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B41868W8337M Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41868Capacitance30µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationAutomotiveApplicationsAutomotiveRipple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.319" (33.50mm)Height - Seated (Max).319" (33.50mm)Surface Mount Land Size-Package / CaseKadia, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageB41868Capacitance330µFColerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41868W8337M
Aluminum Electrolytic CapacitorsPackageRadial, CanStriesB41868Capacitance330µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature90arPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency680mA @ 100kHzImpedance0.295° (7.50mm)Liad Spacing0.630° Dia (16.00mm)Size / Dimension1.319° (33.50mm)Striace Mount Land Size-Mounting TypeFrequencyPackage / CaseKadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41868Capacitance330µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency680mA @ 100kHzImpedance-Lad Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesB41868Capacitance330µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency680mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Poung TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Bipple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.630° Dia (16.00mm)Size / Dimension1.319° (33.50mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Series	B41868
Voltage - Rated63VESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.319" (33.50mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land SizeFrequencePackage / CaseRadial, Can	Capacitance	330µF
Constraint400 mOhm @ 10kHzESR (Equivalent Series Resistance)400 mOhm @ 10kHzLifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Bipple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.319" (33.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Bipple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	63V
Operating Temperature-PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	400 mOhm @ 10kHz
PolarizationPolarApplicationsAutomotiveAipple Current - Low Frequency-Ripple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 150°C
ApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
IT of a constraint of the formation of th	Polarization	Polar
Ripple Current - High Frequency680mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	680mA @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41868W8337M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B41868W8337M Payment Methods





If you have any question about B41868W8337M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com