

# B41888C3398M

Request a Quote

#### B41888C3398M Information

Heisener.com	Part Number	B41888C3398M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 3900UF 20% 10V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
Tor reference only		E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B41888C3398M Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41888Capacitance3900µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzDoparting Temperature10000 Hrs @ 105°COperating Temperature-5°C ~ 105°CPolarizationAutomotiveApplicationsQanobusRipple Current - High Frequency-Lipdance2.53A @ 100kHzImpedance0.295°(7.50mm)Lied Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41888Capacitance3900µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Lied Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B41888C3398M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB41888Capacitance3900µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency253A @ 100kHzImpedance0.255° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41888Capacitance3900µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency253A @ 100kHzImpedance0.255°C r .105°CSize / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB41888Capacitance3900µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Lingedance26 mOhmsLiag Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance3900µFCapacitance±20%Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Lingedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - High Frequency-Lided Spacing26 mOhmsImpedance269 mOhmsLead Spacing0.630° Dia (16.00mm)Size / Dimension0.866° (22.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B41888
Voltage - RatedIOVESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsAutomotiveRipple Current - Low Frequency-Stage Low Frequency253A @ 100kHzImpedance26 mOhmsLead Spacing0.630° Dia (16.00mm)Size / Dimension0.866° (22.00mm)Height - Seated (Max)0.866° (22.00mm)Surface Mount Land Size-Pounting TypeRatial, Can	Capacitance	3900µF
ESR (Equivalent Series Resistance)29 mOhm @ 10kHzLifetime @ Temp.10000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarPolarApplicationsAutomotiveApple Current - Low Frequency-Kipple Current - High Frequency2.53A @ 100kHzImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.660" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 105°CDoperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Linpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pounting TypeRadial, Can	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency2.53A @ 100kHzImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	29 mOhm @ 10kHz
PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency2.53A @ 100kHzImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
ApplicationsAutomotiveApplications-Ripple Current - Low Frequency2.53A @ 100kHzRipple Current - High Frequency26 mOhmsImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
IIRipple Current - Low Frequency-Ripple Current - High Frequency2.53A @ 100kHzImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency2.53A @ 100kHzImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
In rest of the problem26 mOhmsImpedance26 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2.53A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	26 mOhms
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### B41888C3398M Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B41888C3398M Payment Methods





If you have any question about B41888C3398M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com