



B41888D6157M Information

Manufacturer EPCOS (TDK) Category Heisener.com

Capacitors **Aluminum Electrolytic Capacitors**

Description CAP ALUM 150UF 20% 50V RADIAL

Package

For the pricing/inventory/lead time, please contact

Part Number B41888D6157M

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41888D6157M Specifications

Manufacturer Part Number B41888D6157M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41888 Capacitance 150µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Oparization Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.352" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41888 Capacitance 150µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 10s°C Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Mippedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B41888D6157M
Aluminum Electrolytic Capacitors Package Radial, Can Series B41888 Capacitance 150µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41888 Capacitance 150μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41888 Capacitance 150µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 150μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B41888
Voltage - Rated 50V ESR (Equivalent Series Resistance) 228 mOhm @ 10kHz Lifetime @ Temp. 7000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Capacitance	150μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ead Spacing Outer of Johnson Lead Spacing Outer of Johnson Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar Automotive -000 Hrs @ 105°C -000 Hrs @ 105°C -000 Hrs @ 105°C -015°C -015°C -015°C -015°C -015°C -015°C -015°C -010°C -0	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	50V
Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	228 mOhm @ 10kHz
Polarization Applications Automotive Ripple Current - Low Frequency	Lifetime @ Temp.	7000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - 600mA @ 100kHz Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance 203 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	600mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	203 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.532" (13.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41888D6157M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41888D6157M Payment Methods



















B41888D6157M Shipping Methods













If you have any question about B41888D6157M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com