



### **B41888D8687M Information**

Heisener.com

Part Number B41888D8687M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 680UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B41888D8687M Specifications**

Manufacturer Part Number         B41888D8687M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B41888           Capacitance         680μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Operating Temperature         -55°C ~ 105°C           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can           Report errors?	<b>L</b>	
Category         Capacitors           Package         Radial, Can           Series         B41888           Capacitance         680µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	B41888D8687M
Package         Radial, Can           Series         B41888           Capacitance         680µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	EPCOS (TDK)
Package         Radial, Can           Series         B41888           Capacitance         680μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         B41888           Capacitance         680µF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         680μF           Tolerance         ±20%           Voltage - Rated         63V           ESR (Equivalent Series Resistance)         77 mOhm @ 10kHz           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         1.46A @ 100kHz           Impedance         70 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 63V  ESR (Equivalent Series Resistance) 77 mOhm @ 10kHz  Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications Automotive  Ripple Current - Low Frequency - Ripple Current - High Frequency 1.46A @ 100kHz  Impedance 70 mOhms  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	B41888
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.46A @ 100kHz  Impedance  70 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Riowood High Temperature  77 mOhm @ 10kHz  10000 Hrs @ 105°C  10000 Hrs @ 10000 Hrs @ 1000  10000 H	Capacitance	680μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Oceanication  No mohms  Lead Spacing  Oceanication  Oceanica	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  To mOhms  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Polar  -55°C ~ 105°C  -105°C  -10	Voltage - Rated	63V
Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  70 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	ESR (Equivalent Series Resistance)	77 mOhm @ 10kHz
Polarization Polar Applications Automotive  Ripple Current - Low Frequency - Ripple Current - High Frequency 1.46A @ 100kHz Impedance 70 mOhms  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency - Ripple Current - High Frequency 1.46A @ 100kHz Impedance 70 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - 1.46A @ 100kHz Impedance 70 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 70 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance70 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.46A @ 100kHz
Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	70 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **B41888D8687M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B41888D8687M Payment Methods**



















## **B41888D8687M Shipping Methods**













If you have any question about B41888D8687M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com