



B41889A3687M8 Information

Heisener.com

Part Number B41889A3687M8
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 680UF 20% 10V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com

com Request a Quote



Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41889A3687M8 Specifications

Manufacturer Part Number B41889A3687M8 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41889 Capacitance 680µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 460 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B41889 Capacitance 680µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 460 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.532" (13.50mm) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	B41889A3687M8
Package Radial, Can Series B41889 Capacitance 680µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 460 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Delar Purpose Ripple Current - Low Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB41889Capacitance680μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)460 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.54A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series B41889 Capacitance 680μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 460 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 680μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 460 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)460 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.54A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	B41889
Voltage - Rated10VESR (Equivalent Series Resistance)460 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.54A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	680μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Redial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Inspedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C - Cannot an experiment of the company of t	Voltage - Rated	10V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Inspedance Lead Spacing Outer of Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar Folar General Purpose Folar General Purpose 1.54A @ 100kHz 1.54A @ 100kHz	ESR (Equivalent Series Resistance)	460 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency - 1.54A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.532" (13.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	1.54A @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.532" (13.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.532" (13.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report crists:		Report errors?

B41889A3687M8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41889A3687M8 Payment Methods





















B41889A3687M8 Shipping Methods













If you have any question about B41889A3687M8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com