



B41889A4108M8 Information

Ma Ca Heisener.com

Part Number B41889A4108M8
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 16V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B41889A4108M8 Specifications

Manufacturer Part Number B41889A4108M8 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B41889 Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
CategoryCapacitorsPackageRadial, CanSeriesB41889Capacitance1000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency2A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B41889A4108M8
Package Radial, Can Series B41889 Capacitance 1000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B41889 Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B41889 Capacitance 1000μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 1000µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 270 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polar Applications General Purpose Ripple Current - Low Frequency - Carrent - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Through Hole Package / Case Raistance) 16V 270 mOhm @ 120Hz 270 mOhm @ 12	Series	B41889
Voltage - Rated16VESR (Equivalent Series Resistance)270 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency2A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 270 mOhm @ 120Hz 2000 Hrs @ 105°C - Connect Section General Purpose - Lad 100kHz - Lad 100kHz - Lad 1000mm) 0.394" Dia (10.00mm) 0.669" (17.00mm) Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C - Cancel Purpose General Purpose - 2A @ 100kHz - 0.197" (5.00mm) 0.394" Dia (10.00mm) 0.669" (17.00mm) Through Hole Radial, Can	Voltage - Rated	16V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 2A @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Nize / Dimension O.394" Dia (10.00mm) Height - Seated (Max) O.669" (17.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	270 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency - 2A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.669" (17.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	2A @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.669" (17.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.669" (17.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B41889A4108M8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B41889A4108M8 Payment Methods



















B41889A4108M8 Shipping Methods













If you have any question about B41889A4108M8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com