

### **B43041A5226M Information**

Heisener.com

Part Number B43041A5226M Manufacturer EPCOS (TDK) Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 22UF 20% 450V RADIAL

**Package** 

For the pricing/inventory/lead time, please contact

For Reference Only E-mail: salesdept@heisener.com

Website: https://www.heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43041A5226M Specifications**

Manufacturer Part Number         B43041A5226M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B43041           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can           Report errors?	<b>L</b>	
Category         Capacitors           Package         Radial, Can           Series         B43041           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	B43041A5226M
Package         Radial, Can           Series         B43041           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	EPCOS (TDK)
Package         Radial, Can           Series         B43041           Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         B43041           Capacitance         22µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         22μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         105mA @ 120Hz           Ripple Current - High Frequency         210mA @ 100kHz           Impedance         -           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 105mA @ 120Hz Ripple Current - High Frequency 210mA @ 100kHz  Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	B43041
Voltage - Rated 450V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 105mA @ 120Hz  Ripple Current - High Frequency 210mA @ 100kHz  Impedance -  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Capacitance	22μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  105mA @ 120Hz  Ripple Current - High Frequency  210mA @ 100kHz  Impedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  1.063" (27.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  105mA @ 120Hz  Rippedance  -  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Voltage - Rated	450V
Operating Temperature Polarization Polar  Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar  Ripple Current - High Frequency Ripple Current - High Frequency Polar  Ripple Current - Low Frequency Polar  Ripp	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 105mA @ 120Hz  Ripple Current - High Frequency 210mA @ 100kHz  Impedance -  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  210mA @ 120Hz  210mA @ 100kHz  Impedance  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 210mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - Low Frequency	105mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	210mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **B43041A5226M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43041A5226M Payment Methods**



















## **B43041A5226M Shipping Methods**













If you have any question about B43041A5226M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com