

B43044A1107M

Request a Quote

B43044A1107M Information

Heisener.com	Part Number	B43044A1107M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 100UF 20% 160V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
Tor Reference Only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43044A1107M Specifications

Manufacturer Part Number B430441107M Manufacturer EPCOS (TDK) Category Capacitors Alminum Electrolytic Capacitors Alminum Electrolytic Capacitors Package Radial, Can Streis B43044 Capacitance Idu/IA Orleance Ja004 Streise Resistance) 20% Voltage - Rated IdOV ESR (Equivalent Series Resistance) - Operating Temperature 5000 Hrs © 105°C Operating Temperature Solow Hrs © 105°C Operating Temperature - Applications General Purpose Applications Identify Purpose Streige During High Frequency - Impedance 20% Ordonmin Impedance 20% Ordonmin Isigle Scated (Max) Solow Hrs © 105°C Streige During High Frequency - Impedance - Impedance - Isigle Scated (Max) Solow Frequency Streige During Higherequency - Is	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance100µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance270 mOhmsLiad Spacing0.295" (7.50mn)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Nounting TypeFrough HolePackage / CaseKadial, Can	Manufacturer Part Number	B43044A1107M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance100µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105 °COperating Temperature90larApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100kHzImpedance270 mOhmsLided Spacing0.295 "(7.50mm)Size / Dimension0.630" Dia (1.600mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFarcuga KataPackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43044Capacitance100µFTolerance-20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating TemperaturePolarPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency270 mOhmsLided Spacing0.295° (7.50mm)Size / Dimension1.063° (21.00mm)Size / Dimension1.063° (21.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB4304Capacitance100µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRippe Current - Low Frequency-Impedance270 mOhmsLiad Spacing0.295° (7.50mm)Size / Dimension0.600° Dia (16.00mm)Surface Mount Land Size-Munting Type-Polaring Type-Surface Mount Land Size-Surface Mount Land Size-Mounting Type-Polaring Type-Surface Mount Land Size-Mounting Type-Polaring Type-Polaring Type-Surface Mount Land Size-Polaring Type-Polaring Type </td <td></td> <td>Aluminum Electrolytic Capacitors</td>		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLiad Spacing0.295° (7.50mm)Size / Dimension1.063° Dia (16.00mm)Sizer Addutt Land Size1.063° (27.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial Can	Package	Radial, Can
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance270 mOhmsIngedance0.295° (7.50mn)Size / Dimension0.603° Dia (16.00mn)Size / Dimension1.063° (27.00mn)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseKalia, Can	Series	B43044
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Migned Reg1.28A @ 100kHzImpedance207 mOhmsLead Spacing0.630° Dia (16.00mm)Size / Dimension1.063° (27.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeFrequencePackage / CaseRatial, Can	Capacitance	100µF
ConstructionESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.630° Dia (16.00mm)Size / Dimension1.063° (27.00mm)Height - Seated (Max)-Nurface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFundenteePackage / CaseRadial, Can	Voltage - Rated	160V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeApplications-Ripple Current - Low Frequency1.28A @ 100kHzMipedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseKadi J Can	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can	Polarization	Polar
Ripple Current - High Frequency1.28A @ 100kHzImpedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance270 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
I card Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.28A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	270 mOhms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43044A1107M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43044A1107M Payment Methods





If you have any question about B43044A1107M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com