

B43044A4686M

Request a Quote

B43044A4686M Information

Heisener.com	Part Number	B43044A4686M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 68UF 20% 350V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
FOR REFERENCE ONLY		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43044A4686M Specifications

Manufacturer Part NumberB43044A686MManufacturer QEPCOS (TDK)CategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance6&µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-ApplicationsGeneral PurposeAppleactions1.1 A@ 100kHzImpedance0.295° (7.50mm)Lifetime Signing0.307 Dial (3.50mm)Signing Current - High Frequency0.307 Dial (3.60mm)Lifetime Signing0.307 Dial (3.50mm)Signing Current Jeng0.307 Dial (3.50mm)Signing Current Jeng1.1 A@ 100kHzImpedance0.307 Dial (3.50mm)Lifetim Signing0.307 Dial (3.50mm)Signing Current Jeng1.31° (3.50mm)Signing Current Jeng1.307 Dial (3.50mm)Signing Current Jeng-Signing Current Jeng1.307 Dial (3.50mm)Signing Current Jeng-Signing Current Jeng<		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance68µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43044A4686M
IdentifyAluminu Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance68µFTolerance20%Voltage - Rated350VESR (Equivalent Series Resistance)-Operating Temperature5000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CApplicationsPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.1A @ 100 HrzImpedance0.295° (7.50mm)Siz / Dimension0.300° Dia (1.600mm)Hight - Seated (Max)3.19° (3.50mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseMaila, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43044Capacitance68µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature5000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.1A @ 100kHzImpedance0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseKadial, Can	Category	Capacitors
NoteB4304Capacitance68μFColerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLad Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Polaring Type-Surface Mount Land Size-Mounting Type-Polaring Type-Stace J CaseKaidi, Can		Aluminum Electrolytic Capacitors
Capacitance 68μF Capacitance ±20% Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance 490 mOhms Lead Spacing 0.295° (7.50mm) Size / Dimension 0.300° Dia (16.00mm) Height - Seated (Max) 3.19° (33.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.630° Dia (16.00mm)Size / Dimension1.319° (33.50mm)Hight - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B43044
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.630" Dia (16.00mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can	Capacitance	68µF
ConstraintESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.295° (7.50mm)Size / Dimension1.319° (33.50mm)Height - Seated (Max)-Mounting TypeFrequencyPackage / CaseRidial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeRadia, Can	Voltage - Rated	350V
And Antion Operating Temperature Polar Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.1A @ 100kHz Impedance 490 mOhms Icad Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.1A @ 100kHzImpedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeApplications-Ripple Current - Low Frequency-Mipedance1.1A @ 100kHzImpedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency1.1A @ 100kHzImpedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.1A @ 100kHzImpedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance490 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.1A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	490 mOhms
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43044A4686M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43044A4686M Payment Methods





If you have any question about B43044A4686M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com