



B43044A5127M Information

Heisener.com

Part Number B43044A5127M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 120UF 20% 450V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43044A5127M Specifications

Manufacturer Part Number B43044A5127M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B43044 Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) - Uifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Operating Temperature - Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Die vinite 12/1/12 Specifications	
CategoryCapacitorsPackageRadial, CanSeriesB43044Capacitance120μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	B43044A5127M
Package Radial, Can Series B43044 Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43044 Capacitance 120μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105 °C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43044 Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Round - Ripple Current - Besistance - Ripple Current - Ripple Current - Ripple Current - High Frequency - Through Hole Radial, Can	Series	B43044
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Poon Height - Seated (Max) Ratiol A50V South A50V Concert A50V Con	Capacitance	120μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar 5000 Hrs @ 105°C General Purpose - General Purpose - - - - - - - - - - - - -	Tolerance	±20%
Lifetime @ Temp. Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 105°C General Purpose	Voltage - Rated	450V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose - Cancel Purpose - Through Hole Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case General Purpose - General Purpose - Through Hole Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	-
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	-
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43044A5127M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43044A5127M Payment Methods



















B43044A5127M Shipping Methods













If you have any question about B43044A5127M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com