



B43044F2107M Information

Manufacturer EPCOS (TDK) Category Heisener.com

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 250V RADIAL

Package

Part Number B43044F2107M

For the pricing/inventory/lead time, please contact

Capacitors

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43044F2107M Specifications

Manufacturer Part Number B43044F2107M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B43044 Capacitance 100µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Pagical Cons	2 ie o i ii 210/iii specifications	
Category Capacitors Package Radial, Can Series B43044 Capacitance 100µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	B43044F2107M
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43044Capacitance100μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.4A @ 100kHzImpedance630 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43044 Capacitance 100µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series B43044 Capacitance 100μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105 °COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.4A @ 100kHzImpedance630 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Series	B43044
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency1.4A @ 100kHzImpedance630 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 630 mOhms Lead Spacing Size / Dimension Neight - Seated (Max) Surface Mount Land Size Mounting Type 5000 Hrs @ 105°C - 0.000 Hrs @ 105°C 0.000 Hr	Voltage - Rated	250V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Gan mOhms Lead Spacing October / T.50mm Size / Dimension October / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type - Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Operating Temperature	-
Ripple Current - Low Frequency Ripple Current - High Frequency 1.4A @ 100kHz Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 630 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size Mounting Type Through Hole	Applications	General Purpose
Impedance630 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	-
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - High Frequency	1.4A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	630 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type 1.319" (33.50mm) - Through Hole	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.319" (33.50mm)
	Surface Mount Land Size	-
Padia Can	Mounting Type	Through Hole
rackage / Case Radiai, Can	Package / Case	Radial, Can
Report errors?		Report errors?

B43044F2107M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43044F2107M Payment Methods





















B43044F2107M Shipping Methods













If you have any question about B43044F2107M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com