

B43082A1336M

Request a Quote

B43082A1336M Information

Heisener.com	Part Number	B43082A1336M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 33UF 20% 160V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
Tor Reference Only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43082A1336M Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43082Capacitance33µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency5000 Aft @ 100 KHzImpedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43082Capacitance33µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency500m A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	B43082A1336M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43082Capacitance33µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43082Capacitance33µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ripple Current - High Frequency0197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesB43082Capacitance33µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Toterance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stop Age 100k Hz5000 Hrs @ 100k HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	B43082
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stopperature5000 A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.304" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseSatial Can	Capacitance	33µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeAiple Current - Low Frequency-Kipple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFracupationPackage / CaseRatial, Can	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stop A @ 100kHz-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeForage Academic State	Voltage - Rated	160V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Sigple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeFuncy HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency500mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	500mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43082A1336M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43082A1336M Payment Methods





If you have any question about B43082A1336M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com