

B43082A2686M Information

Manufacturer EPCOS (TDK) Category Capacitors Heisener.com

Aluminum Electrolytic Capacitors

Description CAP ALUM 68UF 20% 200V RADIAL

Package

For the pricing/inventory/lead time, please contact

Part Number B43082A2686M

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43082A2686M Specifications

Manufacturer Part Number B43082A2686M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can Series B43082 Capacitance 68µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Operating Temperature - Oplarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	I .	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B43082 Capacitance 68µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	B43082A2686M
Package Radial, Can Series B43082 Capacitance 68μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	EPCOS (TDK)
Package Radial, Can Series B43082 Capacitance 68μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series B43082 Capacitance 68µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 68μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43082
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Tempedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 200V - 1000 - 10	Capacitance	68μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature - Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 760mA @ 100kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 8000 Hrs @ 105°C - 1000 Hrs @ 1000	Tolerance	±20%
Lifetime @ Temp. Operating Temperature - Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 5000 Hrs @ 105°C - Commanded - Commanded	Voltage - Rated	200V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Ripple Current - High Frequency Room A @ 100kHz Impedance - Lead Spacing O.197" (5.00mm) Size / Dimension O.492" Dia (12.50mm) Height - Seated (Max) I.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency - 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose - 0.100kHz - 1.000mA @ 100kHz - 1.	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency 760mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	760mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43082A2686M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43082A2686M Payment Methods



















B43082A2686M Shipping Methods













If you have any question about B43082A2686M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com