

#### **B43086A2476M Information**

Heisener.com

For Reference Only

Part Number B43086A2476M
Manufacturer EPCOS (TDK)
Category Capacitors

Capacitors
Aluminum Electrolytic Capacitors

**Description** CAP ALUM 47UF 20% 200V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43086A2476M Specifications**

Manufacturer Part Number         B43086A2476M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can           Series         B43086           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Operating Temperature         -           Oplarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	<b>L</b>	
Category         Capacitors           Package         Radial, Can           Series         B43086           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	B43086A2476M
Package         Radial, Can           Series         B43086           Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	EPCOS (TDK)
Package         Radial, Can           Series         B43086           Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         B43086           Capacitance         47µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         47μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         10000 Hrs @ 105°C           Operating Temperature         -           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         528mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         0.866" (22.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 200V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C  Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 528mA @ 100kHz  Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	B43086
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 105°C  Operating Temperature  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Feducate  Lead Spacing  10000 Hrs @ 105°C  General Purpose  -  10000 Hrs @ 105°C  Foliar  Folia	Capacitance	47μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Fead Spacing  Onerating  Onerating Temperature  -  Lead Spacing  Onerating Temperature  Onerating Temperature  -  Lead Spacing  Onerating Temperature  Onerating Temperature  Onerating Temperature  Onerating Temperature  -  SumA @ 100kHz  Impedance  Onerating Temperature  Onerating Tempera	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  - Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  10000 Hrs @ 105°C  General Purpose  -  10000 Hrs @ 105°C  10000 Hrs @ 10000	Voltage - Rated	200V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Federal Purpose Ripple Current - High Frequency Federal Purpose  1.	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency	Lifetime @ Temp.	10000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency - Ripple Current - High Frequency 528mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-
Ripple Current - Low Frequency - S28mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.492" Dia (12.50mm)  Height - Seated (Max)  0.866" (22.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	528mA @ 100kHz
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 0.866" (22.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **B43086A2476M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43086A2476M Payment Methods**

































If you have any question about B43086A2476M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com