

B43088A5226M

Request a Quote

B43088A5226M Information

Heisener.com	Part Number	B43088A5226M	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 22UF 20% 450V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43088A5226M Specifications

Manufacturer Part Number B43088A5226M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series B43088 Capacitance Series Olerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Operating Temperature 20000 Hrs @ 105°C Operating Temperature - Operating Temperature - Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 0295°T, 50mm) Size / Dimension 630°D inal (6.00mm) Height - Seated (Max) 503°C in Common Surface Mount Land Size - Mounting Type Finough Hele	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43088Capacitance22µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Nounting TypeFinough HolePackage / CaseMain, Can	Manufacturer Part Number	B43088A5226M
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesB43088Capacitance22µFTolerance±20%Voltage - Rated60000 Hrs @ 105°CESR (Equivalent Series Resistance)00000 Hrs @ 105°COperating Temperature00000 Hrs @ 105°COperating Temperature0ApplicationsGeneral PurposeRipple Current - Low Frequency6000A HrzImpedance0.295° (7.50mm)Size / Dimension0.630° Dia (1.600mm)Size / Dimension0.630° Dia (1.600mm)Height - Seated (Max)1.063° (7.200mm)Surface Mount Land Size-Mounting TypeFarcuga HolePackage / CaseRadial, Can	Manufacturer	EPCOS (TDK)
PackageRadial, CanSeriesB43088Capacitance22µFTolerance20%Voltage - Rated850VESR (Equivalent Series Resistance)0000 Hrs @ 105°COperating Temperature20000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency660mA @ 100kHzImpedance.Ster J Dimension0.25° (7.50mm)Sier J Dimension0.63° (7.00mm)Sier J Dimension1.63° (7.00mm)Sier Adount Land Size.Surface Mount Land Size.Surface Mount Land Size.Mounting TypeMaid, CanPackage / CaseRatial, Can	Category	Capacitors
SeriesB43088Capacitance22µFTolerance±20%Voltage Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Mightaphi Enquency-Ided Spacing0.295°(7.50mn)Size / Dimension0.630° Dia (16.00mm)Size / Dimension-Surface Mount Land Size-Munting Type-Polaring Type-Surface Mount Land Size-Surface Mount Land Size <td></td> <td>Aluminum Electrolytic Capacitors</td>		Aluminum Electrolytic Capacitors
Capacitance22µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency560mA @ 100kHzImpedance-Size / Dimension0.295°(7.50mm)Size / Dimension1.063° Dia (16.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Toleance±0%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Mipedance-Lead Spacing0.295°(7.50mm)Size / Dimension1.063°(27.00mm)Hight - Seated (Max)1.063°(27.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can	Series	B43088
Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Mipedance-Inpedance0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)-Nurting TypeFrequencyPackage / CaseMail, Can	Capacitance	22µF
EVE-ESR (Equivalent Series Resistance)-Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stoppart560mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.063° (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Tolerance	±20%
Lifetime @ Temp.20000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-StomA @ 100kHz560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadia, Can	Voltage - Rated	450V
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Stople Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadia, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationGeneral PurposeApplications-Ripple Current - Low Frequency-Ripple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	20000 Hrs @ 105°C
ApplicationsGeneral PurposeApple Current - Low Frequency-Ripple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseKadi (Can)	Operating Temperature	-
Ripple Current - Low Frequency-Ripple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	560mA @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

B43088A5226M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43088A5226M Payment Methods





If you have any question about B43088A5226M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com