

B43231A1227M Information



For Reference Only

Part Number B43231A1227M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 220UF 20% 160V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43231A1227M Specifications

Manufacturer Part Number B43231A1227M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43231 Capacitance 220µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" 01 (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In Report errors?	L	
Category Capacitors Package Radial, Can - Snap-In Series B43231 Capacitance 220µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43231A1227M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43231 Capacitance 220μF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43231 Capacitance 220µF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 220μF Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43231
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Paoo Hrs @ 85°C -40°C ~ 85	Capacitance	220μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Voltage - Rated	160V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency 1.01A @ 120Hz Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 0.866" Dia (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.566A @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose 1.01A @ 120Hz 1.566A @ 20kHz	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.566A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	1.01A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	1.566A @ 20kHz
Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43231A1227M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43231A1227M Payment Methods



















B43231A1227M Shipping Methods













If you have any question about B43231A1227M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com