

B43231A6337M Information

Manufacti Category

Part Number B43231A6337M Manufacturer EPCOS (TDK) Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 500V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43231A6337M Specifications

Manufacturer Part Number B43231A6337M Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43231 Capacitance 330µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In Report errors?	1	
Category Capacitors Package Radial, Can - Snap-In Series B43231 Capacitance 330µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43231A6337M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43231 Capacitance 330μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43231 Capacitance 330µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 330μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43231
Voltage - Rated 500V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Capacitance	330μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.66A @ 120Hz Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -25°C ~ 85	Voltage - Rated	500V
Operating Temperature Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose 1.66A @ 120Hz 2.573A @ 20kHz 1.66A @ 120Hz 2.573A @ 120H	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Lead Spacing Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar General Purpose General Purpose 1.66A @ 120Hz 2.573A @ 20kHz	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 2.573A @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 2.573A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	1.66A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	2.573A @ 20kHz
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43231A6337M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43231A6337M Payment Methods



















B43231A6337M Shipping Methods













If you have any question about B43231A6337M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com