

B43252A2157M Information

Manufactur Category Heisener.com

Part Number B43252A2157M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 150UF 20% 200V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43252A2157M Specifications

Manufacturer Part Number B43252A2157M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43252 Capacitance 150µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In Report errors?	1	
Category Capacitors Package Radial, Can - Snap-In Series B43252 Capacitance 150μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43252A2157M
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43252 Capacitance 150μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43252 Capacitance 150µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 150μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43252
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Paoo Uniter Seated (Max) Rounting Type Through Hole Radial, Can - Snap-In	Capacitance	150μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 976.5mA @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Pof.5mA @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 0.866" Dia (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 630mA @ 120Hz Ripple Current - High Frequency 976.5mA @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 976.5mA @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	630mA @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	976.5mA @ 20kHz
Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43252A2157M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43252A2157M Payment Methods





















B43252A2157M Shipping Methods













If you have any question about B43252A2157M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com