

### **B43252A397M Information**



For Reference Only

Part Number B43252A397M Manufacturer EPCOS (TDK) Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 390UF 20% 315V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43252A397M Specifications**

Manufacturer Part NumberB43252A397MManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance390μFTolerance±20%Voltage - Rated315VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolar
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance $390\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $315V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000  \text{Hrs} \ @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, Can - Snap-InSeriesB43252Capacitance $390μF$ Tolerance $±20%$ Voltage - Rated $315V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 Hrs @ 105°C$ Operating Temperature $-25°C \sim 105°C$
Series $B43252$ Capacitance $390\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $315V$ ESR (Equivalent Series Resistance) $-$ Lifetime @ Temp. $2000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Capacitance $390μF$ Tolerance $±20%$ Voltage - Rated $315V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 Hrs @ 105°C$ Operating Temperature $-25°C \sim 105°C$
Tolerance $\pm 20\%$ Voltage - Rated $315V$ ESR (Equivalent Series Resistance) -  Lifetime @ Temp. $2000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  315V  - 2000 Hrs @ 105°C  -25°C ~ 105°C
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C
Lifetime @ Temp. $2000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Operating Temperature $-25^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Polarization
1 Olai ization
Applications General Purpose
Ripple Current - Low Frequency 1.54A @ 120Hz
Ripple Current - High Frequency -
Impedance -
Lead Spacing 0.394" (10.00mm)
Size / Dimension 1.181" Dia (30.00mm)
Height - Seated (Max) 1.850" (47.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors?

#### **B43252A397M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **B43252A397M Payment Methods**



















## **B43252A397M Shipping Methods**













If you have any question about B43252A397M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com