

B43252A6566M

Request a Quote

B43252A6566M Information

Heisener.com	Part Number	B43252A6566M
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 56UF 20% 500V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43252A6566M Specifications

Manufacturer Part NumberB43252A6566MManufacturer CEPCOS (TDK)CategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, Can - Snap-InScriesB43252Capacitance56µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)3.26" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance56µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43252A6566M
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance56µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43252Capacitance56µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency0.394" (10.0mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43252Capacitance56µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance56µFTolerance±20%Voltage Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency290mA @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Nounting TypeRadial, Can - Snap-In	Series	B43252
Voltage - Rated500VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	56µF
Construction-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzNippe Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeForage Arage AragePackage / CaseRadia, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzBipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	500V
Operating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzMipedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency290mA @ 120HzRipple Current - High Frequency449.5mA @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	290mA @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	449.5mA @ 20kHz
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43252A6566M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43252A6566M Payment Methods





If you have any question about B43252A6566M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com