

B43252B4277M Information

Heisener.com

Part Number B43252B4277M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 350V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43252B4277M Specifications

Manufacturer Part Number B43252B4277M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43252 Capacitance 270µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Operating Temperature -25°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814 A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Package Radial, Can - Snap-In Series B43252 Capacitance 270μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43252B4277M
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43252 Capacitance 270µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43252Capacitance270μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.17A @ 120HzRipple Current - High Frequency1.814A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
Series B43252 Capacitance 270µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43252
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Voltage - Rated	350V
Operating Temperature -25°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 1.17A @ 120Hz Ripple Current - High Frequency 1.814A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.814A @ 20kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	1.17A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	1.814A @ 20kHz
Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43252B4277M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43252B4277M Payment Methods



















B43252B4277M Shipping Methods













If you have any question about B43252B4277M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com