

B43252F2567M

B43252F2567M Information

Heisener.com	Part Number Manufacturer Category Description Package	B43252F2567M EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43252F2567M Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature60arApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lied Spacing3.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseKadia, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43252F2567M
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43252Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43252Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency1.76A @ 120HzRiple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43252Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 560μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.76A @ 120Hz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Size / Dimension - Mounting Type - Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In	Series	B43252
Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Capacitance	560µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pounting TypeRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.76A @ 120HzRipple Current - High Frequency2.728A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.76A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	2.728A @ 20kHz
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43252F2567M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43252F2567M Payment Methods





If you have any question about B43252F2567M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com