



### **B43254B4157M Information**

Heisener.com

Part Number B43254B4157M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 150UF 20% 350V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **B43254B4157M Specifications**

Manufacturer Part Number  Manufacturer  EPCOS (TDK)  Category  Capacitors  Aluminum Electrolytic Capacitors  Package  Radial, Can - Snap-In  Series  B43254  Capacitance  150µF  Tolerance  ±20%  Voltage - Rated  350V  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  -  Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Snap-In  843254  240  240  240  25°C ~ 150µF  25°C ~ 105°C  25°C ~ 105°C	1	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         B43254           Capacitance         150µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         760mA @ 120Hz           Ripple Current - High Frequency         1.178A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -	Manufacturer Part Number	B43254B4157M
Package         Radial, Can - Snap-In           Series         B43254           Capacitance         150µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         760mA @ 120Hz           Ripple Current - High Frequency         1.178A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43254Capacitance150μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency760mA @ 120HzRipple Current - High Frequency1.178A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-	Category	Capacitors
Series         B43254           Capacitance         150μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -25°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         760mA @ 120Hz           Ripple Current - High Frequency         1.178A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -		Aluminum Electrolytic Capacitors
Capacitance       150µF         Tolerance       ±20%         Voltage - Rated       350V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       3000 Hrs @ 105°C         Operating Temperature       -25°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       760mA @ 120Hz         Ripple Current - High Frequency       1.178A @ 20kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.000" Dia (25.40mm)         Height - Seated (Max)       1.260" (32.00mm)         Surface Mount Land Size       -	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -25°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 760mA @ 120Hz  Ripple Current - High Frequency 1.178A @ 20kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -	Series	B43254
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  -  350V  360V  360 105°C  360 A 205°C  360 A 200 120 Hz  360 A 200 Hz  360 A 304 A 300 Hz  360 A 304 A 300 Hz  360 A 300 Hrs @ 105°C	Capacitance	150μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.178A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  -	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 105°C  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  O.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  -25°C ~ 105°C  Polar  -25°C ~ 105°C  Polar  -25°C ~ 105°C  Polar  -25°C ~ 105°C  -25°C ~ 105°	Voltage - Rated	350V
Operating Temperature  -25°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.178A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  -25°C ~ 105°C  General Purpose  760mA @ 120Hz  1.178A @ 20kHz  -  1.260" (32.00mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 760mA @ 120Hz  Ripple Current - High Frequency 1.178A @ 20kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.178A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  -	Operating Temperature	-25°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  1.178A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  -	Polarization	Polar
Ripple Current - High Frequency  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  -	Applications	General Purpose
Impedance	Ripple Current - Low Frequency	760mA @ 120Hz
Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.000" Dia (25.40mm)         Height - Seated (Max)       1.260" (32.00mm)         Surface Mount Land Size       -	Ripple Current - High Frequency	1.178A @ 20kHz
Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  1.260" (32.00mm)  -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	1.000" Dia (25.40mm)
	Height - Seated (Max)	1.260" (32.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

#### **B43254B4157M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **B43254B4157M Payment Methods**





















### **B43254B4157M Shipping Methods**













If you have any question about B43254B4157M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com