

### **B43254F2227M Information**

Manufact Category Heisener.com

Part Number B43254F2227M
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 220UF 20% 250V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43254F2227M Specifications**

Manufacturer Part Number         B43254F2227M           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Snap-In           Series         B43254           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         900mA @ 120Hz           Ripple Current - High Frequency         1.395A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	•	
Category         Capacitors           Package         Radial, Can - Snap-In           Series         B43254           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         900mA @ 120Hz           Ripple Current - High Frequency         1.395A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	B43254F2227M
Aluminum Electrolytic Capacitors  Package Radial, Can - Snap-In  Series B43254  Capacitance 220µF  Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 900mA @ 120Hz  Ripple Current - High Frequency 1.395A @ 20kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Snap-In           Series         B43254           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         90mA @ 120Hz           Ripple Current - High Frequency         1.395A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         B43254           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250∨           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         900mA @ 120Hz           Ripple Current - High Frequency         1.395A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         900mA @ 120Hz           Ripple Current - High Frequency         1.395A @ 20kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.000" Dia (25.40mm)           Height - Seated (Max)         1.063" (27.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 900mA @ 120Hz  Ripple Current - High Frequency 1.395A @ 20kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	B43254
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.395A @ 20kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  R3000 Hrs @ 105°C  -40°C ~ 105°	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.395A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.395A @ 20kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.000" Dia (25.40mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Polar Ripple Current - High Frequency Ripple Current - High Frequency Ripple Current - High Frequency 1.395A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Polar Ripple Current - High Frequency Ripple Current - Low Frequency Rippl	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 900mA @ 120Hz Ripple Current - High Frequency 1.395A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 900mA @ 120Hz Ripple Current - High Frequency 1.395A @ 20kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size - Through Hole  Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	900mA @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.000" Dia (25.40mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	1.395A @ 20kHz
Size / Dimension 1.000" Dia (25.40mm)  Height - Seated (Max) 1.063" (27.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.000" Dia (25.40mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### **B43254F2227M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **B43254F2227M Payment Methods**



















## **B43254F2227M Shipping Methods**













If you have any question about B43254F2227M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com