

B43305A2108M000

B43305A2108M000 Information

Heisener.com	 B43305A2108M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305A2108M000 Specifications

Manufacturer Part NumberB43305A2108M000ManufacturerEPCOS (TDK)CategoryCapacitorsAckageAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.200V frs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Lied Spacing3.304 "(10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Surface Mount Land Size-Mounting TypeThrough HoleNouting TypeThrough HolePanemeerPanemeer	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency.Impedance180 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.866° Dia (22.00mm)Hight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size.Mounting TypeFinough HolePackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43305A2108M000
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzDifferim @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency3.83A @ 100HzLead Spacing0.394" (10.0mm)Size / Dimension8.66" Dia (22.00mm)Hight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Hounting TypeHoraghelePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866° Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzInpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzImpedance180 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Torance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzImpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzImpedance180 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1000µF
C30 mOhm @ 100HzESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866° Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRatial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension2.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	130 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.83A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	180 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Descent our	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

B43305A2108M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A2108M000 Payment Methods





If you have any question about B43305A2108M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com