

B43305A2338M80

B43305A2338M80 Information

Contactence cana tier	 B43305A2338M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 3300UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305A2338M80 Specifications

Manufacturer Part NumberB43305A2338M80ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance3300µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationGeneral PurposeRipple Current - High Frequency4.87A @ 100HzRipple Current - High Frequency55 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia 300mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeBarial Can - Snap-In	-	
CategoryCapacitorsAckageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance3300µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43305A2338M80
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance3300µFTolerance±20%Voltage - Rated000VESR (Equivalent Series Resistance)40 mOhm @ 100HzDerating Temperature2000 Hrs @ 85°COparization40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance3300µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzInpedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesB43305Capacitance3300µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzImpedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzInpedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.44" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Totrance±20%Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzImpedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzMipedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	3300µF
For ESR (Equivalent Series Resistance)40 mOhm @ 100HzESR (Equivalent Series Resistance)4000 Hrs @ 85°CLifetime @ Temp.6000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	40 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency4.87A @ 100HzRipple Current - High Frequency-Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a rank	Applications	General Purpose
Impedance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	4.87A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	55 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole	Height - Seated (Max)	2.244" (57.00mm)
	Surface Mount Land Size	-
Package / Case Radial Can - Snan-In	Mounting Type	Through Hole
Tuonu, cui onup in	Package / Case	Radial, Can - Snap-In
Report en		Report errors?

B43305A2338M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

B43305A2338M80 Payment Methods



B43305A2338M80 Shipping Methods



If you have any question about B43305A2338M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com