

# B43305A2477M67

#### B43305A2477M67 Information

Heisener.com	 B43305A2477M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305A2477M67 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Radial, Can - Snap-In   Package Radial, Can - Snap-In   Series B43305   Capacitance 470µF   Tolerance ±20%   Voltage - Rated 200V   ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 370 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.260" (32.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Kadial, Can - Snap-In		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzImpedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305A2477M67
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.172A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency.172A @ 100HzRiple Current - High Frequency.1Size / Dimension0.394" (10.00mm)Size / Dimension0.366° Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance470µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.72A @ 100HzLied Spacing370 mOhmsImpedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).12c0" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 470µF   Tolerance ±20%   Voltage - Rated 200V   ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 1.72A @ 100Hz   Impedance 370 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.260" (32.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzImpedance370 mOhmsLead Spacing0.866" Dia (22.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land SizeFrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	470µF
ESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzImpedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Pounting TypeRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	270 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.72A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.72A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
InInRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.72A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	370 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43305A2477M67 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305A2477M67 Payment Methods





If you have any question about B43305A2477M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com