



#### B43305A5397M60 Information

Heisener.com

Part Number B43305A5397M60
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 390UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43305A5397M60 Specifications**

Manufacturer Part Number         B43305A5397M60           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         B43305           Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         350 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.09A @ 100Hz           Ripple Current - High Frequency         -           Impedance         490 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.984" Dia (25.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can - Snap-In Series B43305 Capacitance 390µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 350 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43305A5397M60
Package         Radial, Can - Snap-In           Series         B43305           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         350 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.09A @ 100Hz           Ripple Current - High Frequency         -           Impedance         490 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.984" Dia (25.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Snap-In           Series         B43305           Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         350 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.09A @ 100Hz           Ripple Current - High Frequency         -           Impedance         490 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.984" Dia (25.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         B43305           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         350 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.09A @ 100Hz           Ripple Current - High Frequency         -           Impedance         490 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.984" Dia (25.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance       390μF         Tolerance       ±20%         Voltage - Rated       450V         ESR (Equivalent Series Resistance)       350 mOhm @ 100Hz         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       2.09A @ 100Hz         Ripple Current - High Frequency       -         Impedance       490 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       0.984" Dia (25.00mm)         Height - Seated (Max)       2.244" (57.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) 350 mOhm @ 100Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.09A @ 100Hz  Ripple Current - High Frequency -  Impedance 490 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	B43305
Voltage - Rated 450V  ESR (Equivalent Series Resistance) 350 mOhm @ 100Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.09A @ 100Hz  Ripple Current - High Frequency -  Impedance 490 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Capacitance	390µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.09A @ 100Hz  Ripple Current - High Frequency  Impedance  490 mOhms  Lead Spacing  3350 mOhm @ 100Hz  400 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  490 mOhms  Lead Spacing  32244" (57.00mm)  Height - Seated (Max)  2.244" (57.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  -Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 85°C  -40°C ~ 85°C  -40°C	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.09A @ 100Hz  Ripple Current - High Frequency -  Impedance 490 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	350 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.09A @ 100Hz  Ripple Current - High Frequency -  Impedance 490 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose  Ripple Current - Low Frequency 2.09A @ 100Hz  Ripple Current - High Frequency -  Impedance 490 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  490 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.984" Dia (25.00mm)  Height - Seated (Max)  2.244" (57.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.09A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 0.984" Dia (25.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	490 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
Report errors.		Report errors?

#### **B43305A5397M60 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43305A5397M60 Payment Methods





















## B43305A5397M60 Shipping Methods













If you have any question about B43305A5397M60, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com