

B43305A5567M87

B43305A5567M87 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43305A5567M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305A5567M87 Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency2.81A @ 100HzRiple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	_	
CapacitorsPackageRadial, Can - Snap-InPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzLifesting @ Japacing340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305A5567M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ remp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency340 mOhmsSize / Dimension1.81" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseKalia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency241 mOhmsRipple Current - High Frequency340 mOhmsSize / Dimension1.81" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance560μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzLifedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzLifed Spacing340 mOhmsImpedance340 mOhmsIsize / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Poackage / CaseKadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Sigr / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	560µF
Constraint240 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°CLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	240 mOhm @ 100Hz
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.81A @ 100HzRipple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance340 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.81A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	340 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43305A5567M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A5567M87 Payment Methods





If you have any question about B43305A5567M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com