



B43305A9107M62 Information

Heisener.com

Part Number B43305A9107M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43305A9107M62 Specifications

Manufacturer Part Number B43305A9107M62 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	•	
CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance100μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.36 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency790mA @ 100HzRipple Current - High Frequency-Impedance1.83 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)	Manufacturer Part Number	B43305A9107M62
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 100µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension Aluminum Electrolytic Capacitors Radial, Can - Snap-In - 3 Lead B43305 Ead Snap-In - 3 Lead B4300 Ead Sna	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 100µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Category	Capacitors
Series B43305 Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)		Aluminum Electrolytic Capacitors
Capacitance 100μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.36 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Series	B43305
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency Impedance 1.83 Ohms Lead Spacing 5ize / Dimension 0.866" Dia (22.00mm)	Capacitance	100μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.86 Ohm @ 100Hz 1.86 Ohm @ 100Hz 1.87 Ohm @ 100Hz 1.88 Ohms 1.88 Ohms 1.88 Ohms	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension -40°C ~ 85°C Polar Pola	ESR (Equivalent Series Resistance)	1.36 Ohm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 790mA @ 100Hz Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Applications	General Purpose
Impedance 1.83 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Ripple Current - Low Frequency	790mA @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm)	Ripple Current - High Frequency	-
Size / Dimension 0.866" Dia (22.00mm)	Impedance	1.83 Ohms
	Lead Spacing	0.394" (10.00mm)
11.14 G + 104)	Size / Dimension	0.866" Dia (22.00mm)
Height - Seated (Max) 1.063" (27.00mm)	Height - Seated (Max)	1.063" (27.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43305A9107M62 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A9107M62 Payment Methods



















B43305A9107M62 Shipping Methods













If you have any question about B43305A9107M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com