

# B43305A9397M82

#### B43305A9397M82 Information

Heisener.com	 B43305A9397M82 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 390UF 20% 400V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305A9397M82 Specifications

CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43305Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance0.984" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43305Capacitance390µFColerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzDoperating Temperature2000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance470 mOhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43305A9397M82
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.187A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43305Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance390μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzImpedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)350 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzImpedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	390µF
LJESR (Equivalent Series Resistance)350 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°CLifetime @ Temp40°C ~ 85°COperating TemperaturePolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzNippedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 1.87A @ 100Hz   Ripple Current - High Frequency -   Impedance 470 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.984" Dia (25.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Fhough Hole   Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	350 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.87A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.87A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	470 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### B43305A9397M82 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305A9397M82 Payment Methods





If you have any question about B43305A9397M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com