

# B43305A9567M000

#### B43305A9567M000 Information

Heisener.com Order server carls here	 B43305A9567M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305A9567M000 Specifications

Manufacturer Part NumberB43305A9567M000ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzDerating Temperature2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CPolarizationGeneral PurposeRipple Current - High Frequency2.5A @ 100HzRipple Current - High Frequency303 mOhmsSize / Dimension3.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension-Height - Seated (Max)-Mounting Type-Mounting TypeAradia, Can - Snap-In	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance.330 mOhmsLad Spacing.394" (10.0mm)Size / Dimension1.181" Dia (30.0mm)Height - Seated (Max).Nounting TypeThrough Hole	Manufacturer Part Number	B43305A9567M000
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance330 mOhmsLaed Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB4305Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzDerating Temper2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency30 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)-Mounting TypeThrough Hole	Category	Capacitors
SeriesB43305Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzImpedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance330 mOhmsLead Spacing0.994" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzImpedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)3.50" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	560µF
For ESR (Equivalent Series Resistance)240 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°CLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	240 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Applications	General Purpose
Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	2.5A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	330 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.850" (47.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

#### B43305A9567M000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305A9567M000 Payment Methods





If you have any question about B43305A9567M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com