



B43305A9687M82 Information

(A) Heisener.com

Part NumberB43305A9687M82ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 680UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43305A9687M82 Specifications

Manufacturer Part Number B43305A9687M82 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 680μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency - Lead Spacing 2.94" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.04" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	_	
Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 680μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43305A9687M82
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 680µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance680μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series B43305 Capacitance 680μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance 680μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.83A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	680µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -810°C General Purpose 2.83A @ 100Hz - - - - - - - - - - - - -	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	200 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.83A @ 100Hz Ripple Current - High Frequency - Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 270 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	2.83A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	270 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43305A9687M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A9687M82 Payment Methods



















B43305A9687M82 Shipping Methods













If you have any question about B43305A9687M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com