

B43305A9826M87

lest a Quote

B43305A9826M87 Information

Heisener.com	Part Number	B43305A9826M87	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 82UF 20% 400V SNAP	- 24
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Red

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305A9826M87 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance\$2µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-20mA @ 100HzLifed Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305A9826M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature4.0°C ~ 85°CPolarization70mA @ 100HzRipple Current - Low Frequency6 General PurposeRipple Current - High Frequency-Size / Dimension0.394" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension1.663" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension-Mounting Type-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance82μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzLifedme@.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).1063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Linedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Inmedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzImpedance2.23 OhmsLead Spacing0.866" Dia (22.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	82µF
Comparison1.65 Ohm @ 100HzESR (Equivalent Series Resistance)1.65 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.866" Dia (22.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFacuage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.65 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency720mA @ 100HzRipple Current - High Frequency-Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance2.23 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	720mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	2.23 Ohms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43305A9826M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305A9826M87 Payment Methods





If you have any question about B43305A9826M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com