

B43305B2108M000

B43305B2108M000 Information



Part Number	B43305B2108M000
Manufacturer	EPCOS (TDK)
Category	Capacitors Aluminum Electrolytic Capacitors
Description	CAP ALUM 1000UF 20% 200V SNAP
Package	Radial, Can - Snap-In
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: selesdant@heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B2108M000 Specifications

Manufacturer Part NumberB43305B2108M000ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)30 mOhm @ 100HzOperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance180 mOhms
CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature+40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzImpedance180 mOhms
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance180 mOhms
PackageRadial, Can - Snap-InSeriesB43305Capacitance1000μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzImpedance180 mOhms
SeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency180 mOhms
Capacitance100μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
Voltage - Rated200VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
FSR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
ApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance180 mOhms
Ripple Current - Low Frequency 2.76A @ 100Hz Ripple Current - High Frequency - Impedance 180 mOhms
Ripple Current - High Frequency - Impedance 180 mOhms
Impedance 180 mOhms
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 1.575" (40.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors

B43305B2108M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B2108M000 Payment Methods



If you have any question about B43305B2108M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com