

# B43305B2567M67

Request a Quote

#### B43305B2567M67 Information

Heisener.com	Part Number	B43305B2567M67
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 560UF 20% 200V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305B2567M67 Specifications

Manufacturer Part Number B43305B2567M67   Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43305   Capacitance SofoµF   Tolerance ±20%   Voltage - Rated 200V   ESR (Equivalent Series Resistance) 200 MIm @ 100Hz   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -40°C - 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Inpedance 310 mOhms   Lead Spacing 0.944" Dia (25.00mm)   Size / Dimension -   Mounting Type -   Mounting Type -		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLiad Spacing0.94* (10.00mm)Size / Dimension0.94* Dia (25.00mm)Height - Seated (Max)1.260° (32.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305B2567M67
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.1Impedance310 mOhmsLied Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFarcuage LandPackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature9000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.193A @ 100HzRipple Current - High Frequency.310 mOhmsLead Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.193A @ 100HzLided Spacing0.394" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension.260" (32.00mm)Surface Mount Land Size.Mounting Type.Package / CaseMail, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560μFColerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzImpedance310 mOhmsLead Spacing0.984° (10.00mm)Size / Dimension0.984° Dia (25.00mm)Height - Seated (Max)1.260° (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzImpedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency310 mOhnsLead Spacing0.944" (10.00mm)Size / Dimension1.926" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Hounting TypeFrequencePackage / CaseRatial, Can - Snap-In	Capacitance	560µF
ESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Hight - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	230 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.93A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.93A @ 100Hz
I card Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	310 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43305B2567M67 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305B2567M67 Payment Methods





If you have any question about B43305B2567M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com