

B43305B2827M80

B43305B2827M80 Information

Heisener.com	 B43305B2827M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B2827M80 Specifications

Anufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43305 Capacitance 820µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 0.394" (10.00mm) Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzLifed Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305B2827M80
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance820µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency2.42A @ 100HzRiple Current - High Frequency-Impedance0.394" (10.00mm)Siz / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance0.984" Dia (25.00mm)Liad Spacing0.984" Dia (25.00mm)Size / Dimension1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzLinedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance820µFContract±20%Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Lingedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzLingedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	820µF
ESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzBipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	150 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.42A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance210 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.42A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	210 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43305B2827M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B2827M80 Payment Methods



If you have any question about B43305B2827M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com