

B43305B5127M000

B43305B5127M000 Information

	Constituence com	 B43305B5127M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 120UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact		
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Rec	quest a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B5127M000 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In Package Radial, Can - Snap-In Series B43305 Capacitance 120µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.13 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance 1.59 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance120µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance1.59 OhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305B5127M000
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance120µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLad Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension0.984" Dia (27.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance120µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency970mA @ 100HzRiple Current - High Frequency-Impedance1.59 OhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance120µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension0.984* Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance120μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzLingdance1.59 OhmsLead Spacing0.994" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzImpedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated450VESR (Equivalent Series Resistance)1.13 Ohm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzImpedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFarcage / Case	Capacitance	120µF
ESR 1.13 Ohm @ 100Hz ESR (Equivalent Series Resistance) 1.03 Ohm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 970mA @ 100Hz Ripple Current - High Frequency - Impedance 1.59 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFriough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.13 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency970mA @ 100HzRipple Current - High Frequency-Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance1.59 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	970mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.59 Ohms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43305B5127M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B5127M000 Payment Methods





If you have any question about B43305B5127M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com