

B43305B5157M67

B43305B5157M67 Information

Heisener.com	 B43305B5157M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B5157M67 Specifications

Manufacturer Part NumberB43305B5157M67ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C < 85°CPolarziationGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzLinedance1.27 OhmsLiad Spacing0.394° (10.00mm)Lied Spacing0.394° (10.00mm)Kirer JDimension1.260° (32.00mm)Kirace Mount Land Size-Mounting Type-Mounting Type-Manufacture Andrea-Mounting Type-Manufacture Andrea-Mounting Type-Manufacture Andrea-Mounting Type-Manufacture Andrea-Manufacture Andrea-Mounting Type-Manufacture Andrea-Mounting Type-Manufacture Andrea-Mounting Type-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-Manufacture Andrea-<	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305B5157M67
IdentifyAluminur Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43305Capacitance150µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ S5°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications6 General PurposeRipple Current - High Frequency1.13A @ 100HzLided Spacing0.394" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Hight - Seated (Max)-Mounting TypeFnough HolePackage / CaseStail, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance150µFTolerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature44°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.Impedance1.27 OhmsLead Spacing0.994" Dia (25.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension.Mounting Type-Pokage / CaseSize / CasePostStrice Mount Land SizePostStrice Mount Land SizePostRiogh HolePostRatial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzInpedance1.27 OhmsSize / Dimension0.984" 10.00mm)Size / Dimension1.260" (32.00mm)Kurface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzInpedance1.27 OhmsSize / Dimension0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-<	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzImpedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43305
Voltage - Rated450VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzImpedance.Impedance0.394" (10.00mm)Size / Dinension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	150µF
For ESR (Equivalent Series Resistance)900 mOhm @ 100HzESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	900 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance1.27 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.13A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.27 Ohms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Deport error	Package / Case	Radial, Can - Snap-In
Reporterior		Report errors?

B43305B5157M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B5157M67 Payment Methods





If you have any question about B43305B5157M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com