

B43305B5227M000

B43305B5227M000 Information

Heisener.com	 B43305B5227M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B5227M000 Specifications

Manufacturer Part NumberB43305B5227M000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzOperating Temperature2000 Hrs @ 85°CPolarization900 Hrs @ 85°CApplicationsGeneral PurposeApple Current - Low Frequency1.41A @ 100HzRippe Current - High Frequency570 mOhms	
CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InPackageB43305Capacitance220μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.41A @ 100Hz	
InterpretationAluminu Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance20µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzDiferime @ Tempe.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency.Stander Linge Series1.41A @ 100Hz	
PackageRadial, Can - Snap-InSeriesB43305Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency.Apple Current - High Frequency.	
SeriesB43305Capacitance220μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Capacitance220μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Voltage - Rated450VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
FSR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
ApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Ripple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-	
Ripple Current - High Frequency -	
Impedance 870 mOhms	
Lead Spacing 0.394" (10.00mm)	
Size / Dimension 0.984" Dia (25.00mm)	
Height - Seated (Max) 1.457" (37.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Report	errors?

B43305B5227M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B5227M000 Payment Methods





If you have any question about B43305B5227M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com