

B43305B9227M82

Request a Quote

B43305B9227M82 Information

Heisener.com	Part Number	B43305B9227M82	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 220UF 20% 400V SNAP	
	Package	Radial, Can - Snap-In - 3 Lead	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B9227M82 Specifications

Manufacturer Part NumberB43305B9227M82ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43305SeriesB43305Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency830 mOhmsLead Spacing0.394" (10.00mm)	
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
SeriesB43305Capacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.28A @ 100HzImpedance830 mOhmsLead Spacing0.394" (10.00mm)	
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Voltage - Rated400VESR (Equivalent Series Resistance)620 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
For the constraint of the constr	
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Ripple Current - Low Frequency1.28A @ 100HzRipple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Ripple Current - High Frequency-Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Impedance830 mOhmsLead Spacing0.394" (10.00mm)	
Lead Spacing 0.394" (10.00mm)	
Size / Dimension 0.984" Dia (25.00mm)	
Height - Seated (Max) 1.260" (32.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In - 3 Lead	
Rep	ort errors?

B43305B9227M82 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B9227M82 Payment Methods





If you have any question about B43305B9227M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com